

► **OASIS Combo Wash & Dry Machine**

Revolutionizing Laundry Experience



OASIS X series Combo Wash & Dry Machine — the perfect blend of innovation, performance, and simplicity. Designed to redefine your laundry experience, OASIS delivers a complete wash and dry cycle in less than one hour, without the hassle of transferring clothes between machines.

▼ **Advantages And Benefits**

-  **One-Step Wash & Dry Convenience**
  - Wash and dry in a single machine. Save time and effort with seamless automatic transition between washing and drying cycles.
  - Saves space for compact laundromat layouts.
-  **Superior Cleaning & Drying Performance**

OASIS delivers exceptional wash results and faster drying compared to other combo machines, ensuring cleaner, fresher laundry every time.
-  **Heavy-Duty 300G Washer Construction**

High-speed 300G extraction reduces residual moisture effectively, cutting down drying time and improving energy efficiency.

-  **Front Inlet Hot Air Drying System**

Powerful front air intake ensures strong heat penetration for quicker, more even drying with shorter cycle times.
-  **Reduce Gas Consumption by up to 40%**

Optimized heating and airflow design deliver faster drying with less energy use — helping you save on gas costs without compromising performance.
-  **Industry First Self-Cleaning Lint Filter**

Innovative automatic lint filter cleaning system maintains consistent airflow, enhances drying efficiency, and reduces maintenance costs.

▼ **10-inch Touchscreen Control**

10-inch touchscreen control



Smart status indicator -- Different colored indicator lights represent different operation status.



Model		XHY20	XHY30
Washing capacity	kg	20	30
Drying capacity	kg	12	18
Cylinder diameter	mm	683	774
Cylinder depth	mm	550	580
Cylinder volume	L	201	273
Washing speed	rpm	40-50	40-50
Spin speed	rpm	900	850
G force		308	312
Drive Moto	kw	1.2	2
Fan Motor	kw	0.55	0.55
Gas inlet	inch	1/2	
Gas pressure	kPa	NG 1.0-2.5;LPG 2.3-3.3	
Exhaust	mm	Φ160	Φ160
Exhaust airflow	m <sup>3</sup> /h	501	825
Power supply		220-240VAC @ 50/60Hz 1ph (15A Max)	
Water inlet, hot	inch	3/4	
Water inlet, cold	inch	2 x 3/4	
Chemical flush	inch	3/4	
Auto chemical		4 connections, Optional dosing pump	
Water Pressure	Mpa	0.1 - 0.3	
Dimension WxDxH	mm	960 x 1170 x 1628	1080 x 1289 x 1738
Packing WxDxH	mm	980 x 1190 x 1728	1100 x 1309 x 1838
Weight net	kg	560	740
Weight gross	kg	580	760

\*OASIS preserves the right to change the machines and specifications at any time without prior notice.

**OASIS**<sup>®</sup>