

OASIS®



COMMERCIAL TUMBLE DRYER

Capacity: 2*15/2*20/15/20/25/35kg

High-end commercial and industrial laundry equipment manufacturer.

FEATURES

- Stainless steel cylinder.
- Clad steel front and side panels resist rust and fingerprints.
- Large door with 180° opening.
- Axial airflow.
- Heavy-duty door hinge.
- Inverter drive motor and fan motor.
- Standard reversing cylinder.

Control

- Full-color touchscreen control offers 50 programs for OPL and 3 for vend.
- Multiple languages.
- USB connection and networking capability.

Options



Electric heating, Steam heating or Gas heating.



Contact us for other requests.



- Vend audit data, service audit data and remaining time indicator.
- Payment options available in coin, card, mobile pay, and central payment.

Specifications		SCHG300	SCHG400	HG300	HG400	HG500	HG700
Capacity	kg	2x15	2x20	15	20	25	35
Reversing Drum	/	yes	yes	yes	yes	yes	yes
Cylinder Diameter	mm	774	774	774	774	903	903
Cylinder Depth	mm	655	830	665	775	770	1024
Volume	liter	308x2	390x2	308	364	493	656
Gas Inlet	inch	3/4	3/4	1/2	1/2	1/2	1/2
Steam Inlet	inch	NA	NA	1/2	1/2	1/2	1/2
Steam Outlet	inch	NA	NA	1/2	1/2	3/4	3/4
Compressed air inlet*	mm	NA	NA	8	8	8	8
Exhaust	mm	2x155	2x155	160	160	200	200
Motor Power	kW	2x0.25	2x0.25	0.25	0.25	0.75	0.75
Fan Power	kW	2x0.25	2x0.25	0.25	0.25	0.55	0.55
Electric Heating	kW	2x7.5 / 2x15	2x9 / 2x18	7.5/15	9/18	30	36
Power Supply		220V/50Hz/60Hz/1ph 380V/50Hz/60Hz/3ph					
		Contact us for other voltages					
Door Center to Floor	mm	639/1665	639/1665	982	982	1052	1052
Overall Width	mm	840	840	840	840	978	978
Overall Depth	mm	1046	1225	899	1047	1064	1318
Overall Height	mm	2100	2100	1650	1650	1816	1816
Net Weight	kg	260	320	160	180	230	270
Packing Width	mm	940	940	940	940	1078	1078
Packing Depth	mm	1146	1325	999	1147	1164	1418
Packing Height	mm	2250	2250	1797	1797	1966	1966

* Compressed air inlet only applies to steam heating models.

Oasis preserves the right to change the machines and the specification at any time without prior notice.

