

► XF SERIES HIGH-PERFORMANCE SOFTMOUNT WASHER-EXTRACTOR



Precision-engineered softmount design: industry-leading vibration control, more compact structure, superior fabric care, and service-friendly maintenance.

▼ Advantages And Benefits

- Ⓢ Proprietary multi-point vertical suspension structure absorbs >95% vibration.
- 🔒 New handles and safety door locks for more comfortable operation, simpler maintenance, and enhanced safety.
- ⚙️ Variable-frequency drive for precise control of wash and extraction speeds.
- 🍯 3D honeycomb-shaped drum protects textiles, improves cleanliness and accelerates drainage.
- 🛡️ Corrosion-protected wet-area components for longer service life.

- Ⓢ Triple water seals and oversized drum shaft for durability under extreme conditions.
- 🚪 Extra-large door and ergonomic layout for fast, low-effort loading and easy maintenance.
- 👉 Four-compartment manual dosing with five automatic dosing inlets.

► Options

- ① Steam heating; electric heating; dual heating.
- ② Front-tilt models with 60/100/120 kg capacity.

▼ 7-inch Touchscreen Control

- 50 freely programmable programs
- Multiple languages
- USB program transfer
- Manual/automatic mode switching
- Operating status logging



Rated load weight	Kg	40	60	60 (Tilt)	80	100	100 (Tilt)
Dimension							
Width	mm	1180	1487	1547	1672	1672	1727
Depth	mm	1399	1482	1568	1581	1748	1823
Height	mm	1520	1820	1984	1986	1986	2110
Packing dimension							
Width	mm	1200	1507	1567	1692	1692	1747
Depth	mm	1419	1502	1588	1601	1768	1843
Height	mm	1640	1980	2104	2106	2106	2230
Weight							
Net	kg	1140	1840	2040	2100	2600	2800
Washing drum							
Diameter	mm	903	1078	1078	1240	1240	1240
Depth	mm	626	656	656	673	840	840
Volume	dm ³	400	598	598	812	1014	1014
Opening diameter	mm	423	567	567	682	682	682
Electric							
Voltage		380~415v 3p 50/60Hz			220v 3p 50/60Hz (optional)		
Motor	kW	4	5.5	5.5	5.5	7.5	7.5
Heating Element	kW	30	30	30	30	60	60
Washing							
Washing Speed	RPM	30	30	30	30	29	29
Extraction Speed	RPM	771	706	706	658	658	658
G-Force		300	300	300	300	300	300
Utility connection							
Water inlet (cold/hot)	inch	2*1"	2*1 1/2"	2*1 1/2"	2*1 1/2"	2*1 1/2"	2*1 1/2"
Chemical flushing	inch			3/4"			
Water pressure	Mpa			0.1-0.3			
Temperature Max	°C			90			
Drainage	mm	Φ76	Φ110	Φ110	Φ110	2*Φ110	2*Φ110
Steam connection	inch	3/4"	1"	1"	1"	1"	1"
Steam pressure	Mpa					0.4~0.6	
Compress air connection	mm					Φ8	
Compress air pressure	Mpa					0.4~0.8	

*OASIS preserves the right to change the machines and specifications at any time without prior notice.

OASIS[®]